



Anaerobic connectors are available for factory or field termination applications. They use a two-part epoxy and require a polish. Available connector types include LC, SC, ST, and FC. Each connector is individually bagged with body and ferrule, crimps, and multiple sized boots.

COMPLIANCES

- LC Connectors TIA/EIA-604-10
- SC Connectors TIA/EIA-604-3
- ST Connectors TIA/EIA-604-2
- FC Connectors TIA/EIA-604-4

Fiber Connectors, ORDERING INFORMATION

FC Connectors

| | |
|------------------|--|
| EPC-Y21-S | FC Connector, UPC, Single-mode OS2, ceramic ferrule & metal body, includes 900µm and 2.0mm blue boot |
| EPC-Y28-S | FC Connector, APC, Single-mode OS2, ceramic ferrule & metal body, includes 900µm and 2.0mm green boot |
| EPC-F21-S | FC Connector, UPC, 62.5µm multimode OM1, ceramic ferrule & metal body, includes 900µm and 2.0mm beige boot |
| EPC-E21-S | FC Connector, UPC, 50µm multimode OM2, ceramic ferrule & metal body, includes 900µm and 2.0mm black boot |
| EPC-G21-S | FC Connector, UPC, 50µm multimode OM3/4, ceramic ferrule & metal body, includes 900µm and 2.0mm aqua boot |

LC Connectors

| | |
|------------------|---|
| EPC-Y31-S | LC Connector, UPC, Single-mode OS2, ceramic ferrule, blue body, includes 900µm and 2.0mm blue boot |
| EPC-Y38-S | LC Connector, APC, Single-mode OS2, ceramic ferrule, green body, includes 900µm and 2.0mm green boot |
| EPC-F31-S | LC Connector, UPC, 62.5µm multimode OM1, ceramic ferrule, beige body, includes 900µm and 2.0mm beige boot |
| EPC-E31-S | LC Connector, UPC, 50µm multimode OM2, ceramic ferrule, black body, includes 900µm and 2.0mm black boot |
| EPC-G31-S | LC Connector, UPC, 50µm multimode OM3/4, ceramic ferrule, aqua body, includes 900µm and 2.0mm aqua boot |

ST Connectors

| | |
|------------------|---|
| EPC-Y67-S | ST Connector, UPC, Single-mode OS2, ceramic ferrule & metal body, includes 900µm and 2.0mm blue boot |
| EPC-F67-S | ST Connector, UPC, 62.5µm multimode OM1, ceramic ferrule & metal body, in-cludes 900µm and 2.0mm beige boot |
| EPC-E67-S | ST Connector, UPC, 50µm multimode OM2, ceramic ferrule & metal body, includes 900µm and 2.0mm black boot |
| EPC-G67-S | ST Connector, UPC, 50µm multimode OM3/4, ceramic ferrule & metal body, in-cludes 900µm and 2.0mm aqua boot |
| EPC-G61-S | SC Connector, UPC, 50µm multimode OM3/4, ceramic ferrule, aqua body, includes 900µm and 2.0mm aqua boot |

SC Connectors

| | |
|------------------|---|
| EPC-Y61-S | SC Connector, UPC, Single-mode OS2, ceramic ferrule, blue body, includes 900µm and 2.0mm blue boot |
| EPC-Y68-S | SC Connector, APC, Single-mode OS2, ceramic ferrule, green body, includes 900µm and 2.0mm green boot |
| EPC-F61-S | SC Connector, UPC, 62.5µm multimode OM1, ceramic ferrule, beige body, includes 900µm and 2.0mm beige boot |
| EPC-E61-S | SC Connector, UPC, 50µm multimode OM2, ceramic ferrule, black body, includes 900µm and 2.0mm black boot |
| EPC-G61-S | SC Connector, UPC, 50µm multimode OM3/4, ceramic ferrule, aqua body, includes 900µm and 2.0mm aqua boot |