



Zone distribution boxes are available for both floor and ceiling fiber and copper applications. All zone boxes are highly customizable and fully compatible with IllumiCore® panels and modules including but not limited to Classic, PRM, and LGX.

FEATURES AND BENEFITS

- Customizable length, width, and height are tailored to meet your dimensional requirements
- Custom hole placement is available for optimal trunk and patch cable routing
- Lids can be hinged or removable, both with optional lock and latching features
- Bulkheads are adjustable to ensure proper bend radius routing
- Bulkheads can be built to accept Classic, PRM, and LGX compatible products
- Internal 19" mounting is available for copper patch panels
- Strain relief brackets and raised presses can be strategically installed inside of the zone boxes
- OMNIA pre-terminated trunk cables simply slide and lock into OMNIA compatible brackets without the use of a tool, eliminating the need for cable ties.
- Made of Aluminum

Standard Box

C-24248C144HLWLWH

F-24248C144RLWLBA

Floor and Ceiling, 24 x 24 x 8

Fiber Zone Box – Ceiling, 24 x 24 x 8, 144F Capacity, hinged door, with lock, white finish

Fiber Zone Box – Floor, 24 x 24 x 8, 144F Capacity, removable door, with lock, brushed aluminum

Standard Box, ORDERING INFORMATION

(A)-(B)(C)(DD)(E)(FFF)(GG)(HH)(II)

(A) Zone Type

F Floor
C Ceiling

(DD) Height/Depth

08
10
12
CUS Custom

(FFF) Fiber or Copper Capacity

024
048
072
096
144
288
CUS

(B) Length

24 Standard

(E) Panel/Module Specification

C Classic
L LGX
P PRM
5 Cat5e
6 Cat 6

(C) Width

24 Standard

(GG) Lid Type

RL Removable Lid
HL Hinged Lid

(HH) Lock

WL With Lock
NL No Lock

(II) Finish

BA Brushed Aluminum
PC Powder Coat
WH White Paint